

IN THE CLAIMS

Please amend the claims as follows.

1. (Currently Amended) A method for producing a container for holding pressurized fluid, which container comprises a circumferential wall, a base, and ~~if desired~~ optionally a top, at least the circumferential wall being made from metal, ~~characterized in that wherein~~ the circumferential wall is produced by hydroforming before the base, and ~~if desired~~ optionally the top, are attached to the circumferential wall and wherein the circumferential wall which is to be hydroformed is produced as a tubular blank.
2. (Original) The method as claimed in claim 1, in which the circumferential wall which is to be hydroformed is produced as a tailored ~~tabular~~ tubular blank, ~~preferably~~ optionally as a tailored tubular blank with sections of different thicknesses.
3. (Currently Amended) The method as claimed in claim 1 ~~or 2~~, in which the circumferential walls for two or more containers are hydroformed as a single unit.
4. (Currently Amended) The method as claimed in claim 1, ~~2 or 3~~, in which the circumferential wall, prior to the hydroforming, has a substantially round, oval, triangular, rectangular or square cross section and/or a substantially cylindrical or conical shape.
5. (Currently Amended) The method as claimed in ~~one of the preceding claims~~

claim 1, in which the base and/or the top are made from plastics, preferably from a thermoplastic, more preferably from polyethylene.

6. (Original) The method as claimed in claim 5, in which a container is produced with a base and a top made from plastics material, and the base and the top are connected to one another with the aid of a rigid tie rod.

7. (Original) The method as claimed in claim 6, in which the base, top and tie rod are produced as a single unit.

8. (Currently Amended) The method as claimed in claim 6 ~~or 7~~, in which the rigid tie rod is designed to be at least partially hollow, in order to act as a discharge passage for fluid in the container.

9. (Currently Amended) Method according to ~~one of the preceding claims~~ claim 1, in which the circumferential wall is deformed by hydroforming in such a manner that parts of the circumferential wall can be used as a handle or as an attachment point for a handle which is to be attached.

10. (Currently Amended) The method as claimed in ~~one of the preceding claims~~ claim 1, in which the base₁ and ~~if desired~~ optionally the top₁ are releasably secured to the

circumferential wall.

11. (Currently Amended) A container for holding a pressurized fluid, produced using the method as described in ~~one of the preceding claims~~ claim 1, characterized in that wherein the container has a volume of at least 1 liter and at most 100 liters, preferably a volume of at least 5 liters and more preferably a volume of approximately 30 liters.
12. (Original) The container as claimed in claim 11, which is able to withstand a maximum operating pressure of 12 bar, preferably a maximum operating pressure of 6 bar.
13. (Original) Container as claimed in claim 12, in which the circumferential wall has a thickness of between 0.2 and 2.0 mm, preferably between 0.2 and 1.0 mm, depending on the volume of the container.
14. (Currently Amended) The container as claimed in claim 11, ~~12 or 13~~, in which the circumferential wall has a cross section with a dimension of at most 500 mm, preferably at most 400 mm.
15. (Currently Amended) The container as claimed in ~~one of claims 11-14~~ claim 11, which is a beer barrel.

16. (Currently Amended) The container as claimed in ~~one of claims 11-15~~ claim 11, which is designed in such a manner that containers stacked on top of one another fit into one another in nesting fashion.

17. (Currently Amended) The container as claimed in ~~one of claims 11-16~~ claim 11, in which marks are incorporated in the circumferential wall, these marks being formed into the circumferential wall by hydroforming, for example a name, a symbol and/or an instruction.

18. (Currently Amended) The container as claimed in ~~one of claims 11-17~~ claim 11, in which there are deformations in the circumferential wall in order to reinforce the circumferential wall, which deformations are formed in the circumferential wall by hydroforming, for example reinforcing ridges.

19. (Currently Amended) The container as claimed in ~~one of claims 11-18~~ claim 11, in which attachment points are formed integrally in the circumferential wall for connecting pieces for connecting two or more containers, which attachment points are formed by hydroforming.

20. (Currently Amended) The container as claimed in ~~one of claims 11-19~~ claim 11, which is provided with a base and a top made from plastics material, which base and

top are preferably optionally connected to one another by a rigid tie rod.

21. (Currently Amended) The container as claimed in ~~one of claims 11-20~~ claim
11, which is suitable for single use.